

Semi-Custom, FL Series Coaxial Cable

Features:

- *Flexible Equivalent to Semi-Rigid*
- *100+dB Shielding effectiveness*
- *Available using standard Semi-Rigid Connectors*
- *Available using precision 2.4mm, 2.92mm, 3.5mm, SMA, TNC, and N-Type*

	ESM Cable Code	ESM Cable Code
	FL086	FL141
Cable Outer Diameter	0.105"	0.163"
Jacket	FEP	FEP
Outer Conductor	SPC Foil +95% SPC Braid	SPC Foil +95% SPC Braid
Dielectric	PTFE	PTFE
Center Conductor Type	Silver Plated Copper Clad Steel	Silver Plated Copper Clad Steel
Impedance	50	50
VP (%)	70	80
Cutoff Frequency	65	34
Static Bend Radius	.500"	0.750"
Dynamic Bend Radius	10x OD	10x OD
Temperature Range ©	-55 to 200	-55 to 200
Weight (lb/100ft)	1.4	3.2

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF HIGH SPEED INTERCONNECTS, LLC. ANY RE-PRODUCTION, COPY IN PART OR AS A WHOLE *WITHOUT THE WRITTEN PERMISSION OF HIGH SPEED INTERCONNECTS IS STRICTLY PROHIBITED.*